Premium Series 301VS/301BMJ Single Tilt Slider

ing



ENERGY STAR HIGH EFFICIENCY HAUTE EFFICACITÉ

Sustained Excellence

ENERGY STAR HIGH EFFICIENCY HAUTE EFFICACITÉ

Promoter of the Year ENERGY STAR Most Efficient



ENERGY STAR PARTICIPANT





"You'll appreciate the quality we build into every window!"



VERSATILE & FLEXIBLE

For new bomes, these your individual needs with optional nailing




Window Ratings

AAMA/WDMA/CSA101/LS.2/A440-08&11 CSA A440 S1-09 R-PG25 DP 2640pa Water Penetration Resistance w/ screen 220pa no screen 180pa A3 Grade 10 Energy Rating: $+33^* \bullet$ U Value: 0.28(1.59)* Energy Rating: $+41 \bullet$ U Value: 0.18(1.02)* (Triple glazed with Low E and Krypton Gas and a warm edge spacer) CSA Certified • NFRC Certified ENERGY STAR® Qualified • Window Wise Certified USA ENERGY STAR 2016 U.29 SHGC .56 Single Tilt Slider

Style 301VS/301BMJ

Width: Min 18"	Max 72"	
Height: Min 12"	Max 50"	
NOTE: If Height is between 12	" and 13", width can be no less	thai
Maximum size with Triple Glass or Keepsafe is 18 sq. ft.		

Wide Selection of Styles and Configurations



Authorized Distributor



Fusion Welded Frame and Sash

Welding creates a fully sealed, continuous profile that eliminates potential air and water penetration through frame and sash corners.

- . Maintenance Free Solid uPVC Vinyl Profiles The multi-chambered design provides structural strength as well as insulating air pockets which reduce heat and cold transfer.
- Integral Pull Rail Permits single sash to be operated with ease.
- Built-in Water Management Systems Carefully engineered independent water management system allows for quick drainage to the exterior.
- Integral Brick Mould with Nail Fin

Ideal for brick and siding applications, offering cleaner details and improved performance (301BMJ only).





Double End Vent Style 301VSEV/301BMJEV Width: Min 42"

SP

Height: Min 12' Max 50" Widths less than 56" must be 1/3, 1/3, 1/3 Widths over 108" must be 1/4, 1/2, 1/4



Optional Internal grills for beauty and distinction.



Flexible dual durometer seals hug the glass from both sides. The system also includes a glazing tape applied to the interior side. The result is an unprecedented barrier against air and water penetration.

- Commercial Glazing Technique Exterior glass stops, combined with the Double Bond Glazing, are more effective in maintaining a well-sealed window.
- High Performance Glass Options

Choose Solar Gain Low E for free solar heat or Solar Shield Low E for reducing solar heat gain. Argon and Krypton Gas fillings will maximize heat savings! KeepSafe Glass is the laminate of choice for security, quiet and safety!

• 7/8" Overall Insulating Glass

Results in superior thermal performance. Our optional high performance triple glass has two 1/4" air spaces. With Krypton Gas and double Solar Shield Low E, this results in a R8.2 (.12U) center glass value.

• Warm Edge Spacer Technology

Only the best warm edge spacers will reduce perimeter condensation on an insulating glass unit, fight mold and increase the comfort of your home.

IGMA Approved

Certification Numbers - Stainless #2521-P, TempSmart™ #2190-0200508G





Triple Seal

Three layers of premium Fin Seal stop air and water as they reduce sound transmission. Benefit from the best sliding seals available!

Double Neoprene Bulbs

Compression style seals close tight where the sash meets the frame and sliding is not required. Our engineers insisted that you get this premium component!

Recessed Tilt Latches

Your operating sash tilts in for easy cleaning from inside your home. Our recessed design maintains a clean and attractive sight line in your window.

Cam Locks

Heavy duty 180 degree locking cams pull your operating sash and frame tightly together for a great seal!

Smart Locks allow you to both unlock and tilt your sash with a single operation.

shoe expansion break-points secures the sash in place.

Hinged Drain Covers Designed to keep bugs out while allowing water to flow to the outside.




As we are constantly improving our products, specifications may have char from those herein. Please contact VWD regarding up-to-date specifications






Smart Lock (Optional)



Quick Lock Shoes When you tilt your sash for cleaning, a secure locking action from multi-directional

Max 120'



* Tested with Low E, Argon Gas and a warm edge spacer *Ask your dealer for details of glass requirements